

Pleated synthetic filter cartridges that resist softening in water-based fluids

Description

Facet FIS Series synthetic filter cartridges provide efficient filtration of fluids in a wide variety of applications, particularly in water based fluids. This range of reliable filter cartridges is used to remove particulate from a broad range of process streams including water based fluids, chemicals and petroleum based fluids. The high performance filter media used in FIS Series filter cartridges will not soften or prematurely plug in water based fluids unlike filter cartridges that use cellulose based filter media.

FIS Series filter cartridges are manufactured using proprietary combinations of polyester and micro-fiberglass filter media to achieve the desired removal rating. The pleated filter media in the FIS Series cartridge is supported by epoxy coated wire to ensure mechanical stability. The use of synthetic and non-woven filter media results in significantly higher dirt holding capacity than similar cartridges that rely solely on cellulose filter media. This cartridge's innovative design delivers higher flow rates at lower initial pressure drops, and longer on-stream life cycles when compared to conventional cellulose filter cartridges of equal efficiency.

Electro-tin plated, spiral center cores and electroplated end caps are standard components. Special configurations are available with a rigid outer cage for increased mechanical strength.



Benefits

- Synthetic medias provide high efficiencies, superior strength and durability.
- Superior performance in water based fluids, resulting in longer life.
- Extended surface area for maximum dirt holding capacity and long life.
- One piece construction reduces downtime, cartridge change-out costs and eliminates filter bypass concerns.
- Retention ratings available from 0.5 to 40 microns.
- Electro-tin plated components help prevent rust and corrosion.
- A variety of adhesives and gasket materials offer a wide range of compatibility.

Applications

- Amines
- Chemicals, Resins, and Solvents
- Coolants
- Cooling and Process Water
- Glycols and Glycol Solutions
- Hydraulic Oils
- Lube Oils & Seal Oils
- Oil and Water Filtration
- Petroleum Refining Applications
- Power Generation
- Pulp and Paper Industry

Filter Sizes & Dimensions

Dimensions (nominal)			
SERIES <i>X = Micron rating</i>	OD (inches)	ID (inches)	LENGTH (inches)
FIS-209-X	2 1/2	1 1/9	9 7/8
FIS-209-X-3	2 1/2	1 1/9	9 2/3
FIS-511-X	4 1/2	1 3/4	11
FIS-518-X-3	4 1/2	2 5/8	18
FIS-618-X	6	3 1/2	18
FIS-636-X	6	3 1/2	36
FIS-718-X	6	2 5/8	18
FIS-718-X-1	6	2 1/4	18
FIS-7618-X	6	2 5/8 x 3 1/2	18
FIS-736-X	6	2 5/8	36
FIS-7636-X	6	2 5/8 x 3 1/2	36

Note: These are standard sizes. Normal delivery is 2-3 weeks ARO. Many other sizes and combinations are available; please contact us for special sizes.

Temperature/Compatibility Guide

Media	Polyester/Micro Glass	Polyester
Maximum Temp.	275° F	275° F
pH Range	3-10	3-10
Petroleum Products	Excellent	Excellent
Chemicals	Good	Good
Aqueous Solutions	Excellent	Excellent

Performance Specifications

ABSOLUTE, BETA 75 REMOVAL, MICRON	0.5	1	3	5	10	15	20	30	40	50	75	100
Polyester/Micro Fiberglass	•	•	•	•								
Polyester					•	•	•	•	•	•	•	•

Materials of Construction

Filter Media Options

0.5-5 µm	Polyester/Micro fiberglass combination, wire backed
10-100 µm	Polyester, wire backed

Metal Components

Center Core	Electro-tin Plated
End Caps (Optional)	Electro-tin Plated
Outer Cage (Optional)	Electro-tin Plated

Gasket Materials

Standard	Buna N
Optional	Vegetable Fiber, Neoprene, Viton®, Non-asbestos Replacement

Adhesives

Thermoset PVC, Urethane, Epoxy

*Viton is a registered trademark of E.I. duPont de Nemours and Company.
Facet is a trademark of CLARCOR.*

Ordering Information

Cartridge Series	Cartridge Dimensions	Micron Rating	Outer Body Designation	Special Features
FIS	718	0.5 µm	P	N-1
FIS	See Filter Sizes and Dimensions Table.	0.5, 1, 3, 5, 10, 15, 20, 30, 40, 50, 75, 100 µm	No Symbol = No Outer Body P = Outer Body	H = Handle J = Non Asbestos N = Neoprene V = Viton -1 = Special ID -3 = Hilco Retrofit