

PERFORMANCE DATA:

MICRON RATING.....	3 NOMINAL
COLLAPSE PRESSURE RATING.....	75 PSID
MAXIMUM TEMPERATURE.....	225 F
DIRECTION OF FLOW.....	OUTSIDE->IN

DIMENSIONAL DATA:

(A) OUTER DIAMETER, TOP.....	4.00"
(B) OUTER DIAMETER, BOTTOM.....	0.00"
(C) INNER DIAMETER, TOP.....	2.25"
(D) INNER DIAMETER, BOTTOM.....	0.00"
(E) LENGTH.....	18.00"
(F) THREAD.....	NONE

PHYSICAL DATA:

TYPE OF ADHESIVE.....	EPOXY
TYPE OF ENDCAP.....	PLATED STEEL
CENTERTUBE.....	PLATED STEEL
TYPE OF MEDIA.....	PAPER
PLATING.....	ELECTROTIN PLATED
OUTER JACKET.....	YES
CONFIGURATION.....	SINGLE OPEN END

PACKAGING DATA:

NUMBER PER CARTON.....	12
WEIGHT OF CARTON.....	27.00 pounds

NOTE 1: RECOMMENDED CHANGEOUT DIFFERENTIAL PRESSURE = 20 PSID